

OFFICE OF THE DRAIN COMMISSIONER

Dale Twing, Drain Commissioner
306 S North St, White Cloud, Michigan 49349
Telephone: (231) 689-7213 Fax: (231) 689-7266



PLAN REQUIREMENTD AND STANDARDS FOR CROSSING, CONNECTION, OR ENCROACHMENT

All persons intending to cross, connect, discharge to, modify, or encroach upon a drain or within a drain easement must apply for and obtain a permit from the Newaygo County Drain Commissioner prior to commencement of any proposed work. Crossing permits are required to cross over or under a drain, or to install a culvert in a drain. Connection permits are required to connect to or tap into an open or enclosed drain or any of its structures for purposes of discharging stormwater. Any use of a drain easement or right of way that will interfere with the operation of the drain or will increase the cost to the drainage district of performing any maintenance or improvement to the drain is deemed to be inconsistent with the easement. In such a case, an Encroachment Agreement may be issued at the discretion of the Drain Commissioner for what is appropriate to maintain and improve the drain.

Work types that require a permit:

- Connection- Open Drain
- Connection- Enclosed Drain (tap-in)
- Culvert Installation
- Bridge Crossing
- Bored Crossing
- Open Cut Crossing
- Drain Clean Out
- Construction Easement
- Encroachment (sheds, fences, hard landscaping, etc.)

Some work may require consultation with an attorney, engineer, or inspector. The applicant will be responsible for any costs associated with outside consultation.

Submission Requirements:

Permit submittals shall include all the following information:

1. A fully completed permit application including appropriate signatures
2. A site plan drawing or sketch with the following information:
 - a. Location of the county drain or drain easements on the property.
 - b. Descriptions of all construction activity within the easement.
 - c. Dimensions and elevations of all facilities being proposed for construction within the drain easement.
 - d. Type of material used for construction within the drain easement.
3. Parcel information can be found here: Newaygo County Map Viewer
<https://arcgisweb.countyofnewaygo.com/portal/apps/webappviewer/index.html?id=6f09e33488614e8eabd2e8a0f006a9be>

OFFICE OF THE DRAIN COMMISSIONER

Dale Twing, Drain Commissioner
306 S North St, White Cloud, Michigan 49349
Telephone: (231) 689-7213 Fax: (231) 689-7266



Culvert or Bridge Crossings

Crossing means going through, under, or over the right of way of an established county drain. All crossings must comply with the requirements in these rules.

1. The drawing shall also include the crossing in both plan and profile perspective showing the vertical separation distance and the width of the drain easements, upstream and downstream elevations, measures to reestablish the stream bank, erosion control on culvert ends. Flared end sections may be required along with additional information including, but not limited to elevations, size of upstream and downstream culverts, and confirmation of elevation of the established drains. Additional information may be required based on site specific conditions.
2. Culvert or bridge crossings may require hydraulic calculations to demonstrate that the crossing will be hydraulically sufficient and not cause harmful interference up or downstream.
3. All culverts and privately owned and installed at the owner's expense.
4. The Drain Commissioner staff may be present to witness construction and shall receive notice three (3) business days before work is to commence.
5. All pipe or bridges shall be installed according to manufacturer's specifications.

Utility Crossings (Bored or Open Cut Crossings)

1. All crossings over a drain will be reviewed on a case-by-case basis.
2. All crossings under open drains must be bored or directional drilled unless special permission is obtained from the Drain Commissioner. Additional standards are required when open cutting.
3. Utilities, including but not limited to gas, electric, and communications, must be at least 48 inches below the elevation of an open drain (the invert elevation for enclosed drains must be used) for the entire width of the easement.
 - a. In some cases, installation 48 inches below the drain may not be feasible within available right-of-way. The applicant shall document and obtain prior written authorization for a variance in vertical separation. In no case shall less than 18 inches of separation be used. All variances will require installation of an accessible handhole and minimum 100 feet of slack loop to relocate the utility.
4. Sanitary sewer must be ductile iron pipe for the full width of the drain crossing.

Connections

1. Requirements for connection shall be made on a case-by-case basis. It is desired that all connections to enclosed drains be made at a manhole or catch basin.
2. Plastic (PVC, HDPE, etc.) stormwater leads connected into manholes, catch basins, or pipes must be cored and lined with a rubber boot. Connections made for concrete pipe may be cored and the joint sealed with a concrete collar and geotextile fabric. Connections to plastic pipe shall be made with pre-manufactured fittings.
3. Outlets to ditches will be placed at the average low water elevation of the watercourse and pointed downstream. Outlet velocities will be non-erosive.
4. The drawings must also show the diameter of the connection pipe, the diameter of the hole to be cored, the type of boot for stormwater leads, the method of connecting to the boot, the

OFFICE OF THE DRAIN COMMISSIONER

Dale Twing, Drain Commissioner
306 S North St, White Cloud, Michigan 49349
Telephone: (231) 689-7213 Fax: (231) 689-7266



location of any other pipes in the structure, and backfill material 6-inches around the pipe for two feet from the structure.

Encroachments

All encroachments in drain maintenance easements for structures or land use changes that impair or impede the maintenance of the drain must be reviewed and approved by the Drain Commissioner. The Drain Commissioner maintains multiple types of easements and allowable encroachments will differ based on type of easement. The Drain Commissioner reserves the right to deny any application for encroachment into an easement.